


## 2m Female Cable

Smart PXL DOT accessory (24V/48V)




### FEATURES

- IP67 Female Amphenol AT Series connector with industrial grade heat shrink for added rigidity.
- 3 core bare end.
- 2-meter round Fire Retardant PVC cable with resistance to UV.
- Compatible with ENTTEC Smart PXL Dots for fast connection.
- Longer cable length available. (contact us for more info)

### SPECIFICATION

IP Rating	IP67 (excl. bare end)
Total Length	2.07m / 81.26in
Core Count	3
Wire Gauge	16AWG
Conductor Size	1.50mm <sup>2</sup>
Conductor stranding	7/0.50mm <sup>2</sup>
Conductor Material	Copper (stranded)
Electrical Resistance	0.03Ω
Shield	Aluminum foil + tinned copper drain wire
Cable Diameter	6.74mm / 0.265in
Minimum Bend Radius	80.88mm / 3.18in
Cable Jacket	FRPVC
UV Resistant	Yes
Connector	Amphenol AT Series Female
Unit Weight	0.135kg / 0.30lbs
Packaging dimensions	Packaged on a custom order basis.
Warranty	3 year return to base manufacturer warranty.

### PIN OUTPUT CONFIGURATION




### CORE IDENTIFICATION CHART

Each Smart PXL string or accessory is comprised of 3 stranded copper cores, the pinout is as follows:

Identifier	24V		48V	
	Function	Pin	Function	Pin
Black core	V-	1	V-	1
White	Data	2	Data	2
Red core	24V DC +	4	48V DC +	3

ENTTEC recommend the use of cable ferrules when connecting non-tinned cable.



### ORDERING INFORMATION

Product	PN
2m Female Cable (24V)	73018
2m Female Cable (48V)	73022

Visit [www.enttec.com](http://www.enttec.com) to browse compatible pixel products and control system components. For any sales requests, OEM enquiries or to give product feedback contact our team at [sales@enttec.com](mailto:sales@enttec.com).

# enttec.com

MELBOURNE AUS / LONDON UK / RALEIGH-DURHAM USA

Due to constant innovation, information within this document is subject to change.

### PHYSICAL DIMENSIONS

