


2m Female Cable

Smart PXL DOT accessory




FEATURES

- IP67 Female Amphenol AT Series connector with industrial grade heat shrink for added rigidity.
- 3 core bare end.
- 2-meter round Fire Retardant PVC cable with resistance to UV.
- Compatible with ENTTEC Smart PXL Dots for fast connection.


SPECIFICATION

| | |
|-----------------------|--|
| IP Rating | IP67 (excl. bare end) |
| Total Length | 2.07m / 81.26in |
| Core Count | 3 |
| Wire Gauge | 16AWG |
| Conductor Size | 1.50mm ² |
| Conductor stranding | 7/0.50mm ² |
| Conductor Material | Copper (stranded) |
| Electrical Resistance | 0.03Ω |
| Shield | Aluminum foil + tinned copper drain wire |
| Cable Diameter | 6.74mm / 0.265in |
| Minimum Bend Radius | 80.88mm / 3.18in |
| Cable Jacket | FRPVC |
| UV Resistant | Yes |
| Connector | Amphenol AT Series Male |
| Unit Weight | 0.135kg / 0.30lbs |
| Packaging dimensions | Packaged on a custom order basis. |
| Warranty | 3 year return to base manufacturer warranty. |

PHYSICAL DIMENSIONS



PIN OUTPUT CONFIGURATION




CORE IDENTIFICATION CHART

Each Smart PXL string or accessory is comprised of 3 stranded copper cores, the pinout is as follows:

| Identifier | Function | Pin on Amphenol AT Series Connector |
|------------|----------|-------------------------------------|
| Black core | V- | 1 |
| White | Data | 2 |
| Red core | 24V DC + | 4 |

ENTTEC recommend the use of cable ferrules when connecting non-tinned cable.



ORDERING INFORMATION

| Product | PN |
|-----------------|-------|
| 2m Female Cable | 73018 |

Visit www.enttec.com to browse compatible pixel products and control system components. For any sales requests, OEM enquiries or to give product feedback contact our team at sales@enttec.com.

enttec.com

MELBOURNE AUS / LONDON UK / RALEIGH-DURHAM USA

Due to constant innovation, information within this document is subject to change.