


2m Extension Cable

Smart PXL DOT accessory




FEATURES

- IP67 Male Amphenol AT Series connector with industrial grade heat shrink for added rigidity.
- IP67 Female Amphenol AT Series connector with industrial grade heat shrink for added rigidity.
- 2-meter round Fire Retardant PVC cable with resistance to UV.
- Compatible with ENTTEC Smart PXL Dots for fast connection.


SPECIFICATIONS

IP Rating	IP67
Total Length	2.11m / 82.76in
Core Count	3
Wire Gauge	16AWG
Conductor Size	1.50mm ²
Conductor stranding	7/0.50mm ²
Conductor Material	Copper (stranded)
Electrical Resistance	0.032Ω
Shield	Aluminum foil + tinned copper drain wire
Cable Diameter	6.74mm / 0.265in
Minimum Bend Radius	80.88mm / 3.18in
Cable Jacket	FRPVC
UV Resistant	Yes
Connector	Amphenol AT Series Male
Unit Weight	0.175kg / 0.39lbs
Packaging dimensions	Packaged on a custom order basis.
Warranty	3 year return to base manufacturer warranty.

PHYSICAL DIMENSIONS




PIN OUTPUT CONFIGURATION



CORE IDENTIFICATION CHART

Each Smart PXL string or accessory is comprised of 3 stranded copper cores, the pinout is as follows:

Identifier	Function	Pin on Amphenol AT Series Connector
Black core	V-	1
White	Data	2
Red core	24V DC +	4



ORDERING INFORMATION

Product	PN
2m Extension Cable	73020

Visit www.enttec.com to browse compatible pixel products and control system components. For any sales requests, OEM enquiries or to give product feedback contact our team at sales@enttec.com.

enttec.com

MELBOURNE AUS / LONDON UK / RALEIGH-DURHAM USA

Due to constant innovation, information within this document is subject to change.